

Tree House

— LEATHER —

H A N D M A D E

H A N D B A G



PRINT OUT THE PATTERN 100 %

**RECOMMENDED LEATHER THICKNESS 6 - 7 oz (2.4mm - 2.8mm)
and 3 - 4 oz. (1.2mm- 1.6 mm) straps to sew the sides of the main body bag**

RECOMMENDED THREADS 1 MM

HARDWARE

Tuck Lock Clasp

Belt buckle 32 mm

Magnetic snap 18 mm

ASSEMBLY FILES

HARDWARE



Place the previously printed pattern on the leather, punch out all the holes for the seams and fasteners then cut out the elements. First, sew or install the fasteners.

Now sew the pocket as pictured below,



when you are done soak the narrow part of the pocket and shape it in a similar way as shown in the photo.



**Sew a pocket to the inside
leather side as I did.**



**It's time now to sew the sides of the bag, do it exactly the same way
as in the pictures below.**



3 - 4 oz.

(1.2mm- 1.6 mm)

**straps to sew the sides
of the main body bag**

Now we will sew the sides to the main part of the bag as shown below.

When we come with the seam to the arc, the seam holes they may not be in one line, but after a certain distance, everything returns to the correct position.



After sewing on the two sides, we can sew it on a flap for the bag, remember to add a strap for closing the bag at the right moment (version of the bag with a buckle) on the pattern you have marked two lines at which point it should be done.



Now is the time for the main strap for the bag: start and finish the hemming as in the pictures below, if finished, sew the strap to the bag.

WELL DONE

