

Sunglasses

case

Pattern




# Sunglasses Case

Its relatively simple project, the tricky bit is to cut out shape without using ruler, you should use firm leather (preferably veg tan) around 1.5mm-2mm to provide glasses right protection and stiffness of a case.

## What you need for this project:

- 1.tools - utility knife, edge beveler, hole puncher 2.5mm - 3mm, Stitch line hole puncher, ruler, tool to set rivets and snap rivet and edge slicker
- 2.Materials- leather 1.5mm - 2mm veg tan leather, 2 rivets, 1 snap rivet, Waxed thread, Fine sandpaper, dye, leather finish, neatsfoot oil, masking tape, cotton cloth and cotton pads.

1 printout page 5 of this document, important is to print in 100% scale, or use option "actual size". Cut the pattern out, you don't need to be precise at this point. Secure it with masking tape to a piece of leather you want to use, be aware is better to work with smaller piece of leather than with whole hide.



2 Punch all holes for nose bit fitment . Then cut out pattern using utility knife or scalpel, I always sharpen my knife before making any cuts even if you fit brand new blade.



3 at this point is good to bevel the edges, sometimes I do that as well after stitching the leather when you correct the edges.



4 it's time to dye our leather, I use cosmetic cotton pads. You can use hair dryer to speed up drying process. When leather is dry apply leather finish



5 punch out stitching holes, I always use compass to mark stitching line. Set it on 2mm and run it along the edge on front and the back. Make sure you make same amount of holes for front and back.




6 now we can fit the snap closure and the rivets for nose bit inside Case. First fit the snap fastener flip nose bit and secure with two rivets, it stiffens the glasses case and make it easier to close,



7 if you got your nose bit fitted as on this picture you are ready for stitching



8 use wax tread and blunt needless to saddle stitch the sides of a glasses case



9 lightly sand the stitched edges and apply tokonole to smooth the edges, then wipe it with cotton cloth and use wooden slicker for gloss finish.



10 form desired shape with wooden slicker, and stretch leather with your finger, then apply leather feed on the outside using cotton cloth, we recommend to use nets foot oil. Leave it to dry. And Your done



**Warning : We don't take any responsibility for injuries caused while crafting good from this pattern.**

